

Goodbye  
Dryness

Highly  
Reliable  
Transformer  
Base Circuit

Ultrasonic  
**Humidifier**  
(Digital Display)



<b>Brand</b>	SUJAY	SUJAY	SUJAY	SUJAY	SUJAY
<b>Model</b>	SUH-3	SUH-6	SUH-12	SUH-18	SUH-24
<b>Misting Capacity</b>	3 L/hr.	6 L/hr.	12 L/hr.	18 L/hr	24 L/hr.
<b>Body</b>	SS304	SS304	SS304	SS304	S.S. Powder Coated / SS304
<b>Power (Watts)</b>	200 W	300 W	600 W	900 W	1200 W
<b>Circuit</b>	<b>Transformer Base</b> (Highly reliable against voltage fluctuations)	<b>Transformer Base</b> (Highly reliable against voltage fluctuations)	<b>Transformer Base</b> (Highly reliable against voltage fluctuations)	<b>Transformer Base</b> (Highly reliable against voltage fluctuations)	<b>Transformer Base</b> (Highly reliable against voltage fluctuations)
<b>Water Level Control</b>	Automatic (Float Type)	Automatic (Float Type)	Automatic (Float Type)	Automatic (Float Type)	Automatic (Float Type)
<b>Humidity Control &amp; Display</b>	Upto 90%	Upto 90%	Upto 90%	Upto 90%	Upto 90%
<b>Supply Voltage</b>	230V, AC 50Hz	230V AC, 50Hz	230V AC, 50Hz	230V AC, 50Hz	230V AC, 50Hz
<b>Working Temp.</b>	5 to 40 Deg C	5 to 40 Deg C	5 to 40 Deg C	5 to 40 Deg C	5 to 40 Deg C
<b>Air Volume</b>	175 M <sup>3</sup> /hr.	175 M <sup>3</sup> /hr.	350 M <sup>3</sup> /hr.	350 M <sup>3</sup> /hr.	700 M <sup>3</sup> /hr.
<b>Water Quality</b>	TDS<100PPM (DM.Water Ideal)	TDS<100PPM (DM.Water Ideal)	TDS<100PPM (DM.Water Ideal)	TDS<100PPM (DM.Water Ideal)	TDS<100PPM (DM.Water Ideal)
<b>Net Weight</b>	22 kg	23 kg	35 kg	38 kg	55 kg
<b>Castor Wheel</b>	Optional (Extra)	Optional (Extra)	Yes	Yes	Yes
<b>Dimension (inch) (LXBXH)</b>	25 X 17 X 14	25 X 17 X 14	29 X 17 X 17	29 X 17 X 17	33 X 28 X 17

Trust SUJAY Inc.

for Quality, Reliability and Affordability

High  
Capacity  
models mfg  
based on  
Application